

All-Terrain T/A[®]KO

BF Goodrich[®]
Tires
TAKE CONTROL[®]

The all-terrain that KOs the competition.

What it is: The tire that invented the all-terrain category remains the race-winning standard for on- and off-road performance, great mileage and a bold look that transforms the appearance of any vehicle you put it on.

Who it's for: Pickup, jeep and SUV owners who want to step up in looks and true all-terrain on- and off-road performance from their original equipment tires.


Features:

- ShoulderLock™ technology (upper sidewall traction bars, 40% wider shoulder grooves)
- Dual-tread radius with advanced profile design
- Aggressive, high-void all-terrain tread design with interlocking tread elements, innovative siping and stabilized tread center
- Three-ply polyester carcass—TriGard® construction
- Two full-width steel belts
- Rim Protector
- Dual-compound tread
- High-strength single strand bead construction
- Raised white letter and black sidewall styling

Benefits:

- Maximized "aired-down" traction and steering control in deep dirt, mud and sand; more aggressive appearance; reduced noise; minimized hydroplaning^{††}
- Improved stress distribution (up to 12% increase in treadlife); enhanced resistance to irregular wear; better traction^{††}
- Excellent traction and handling on- and off-road; improved traction; and decreased stone retention^{††}
- Exceptional bruise resistance under the tread and in the sidewall
- Stiffer tread area for precise steering response and better cornering control; excellent puncture and bruise resistance^{††}
- Helps protect wheel and tire from off-road hazards, especially during aired-down driving
- Long life and increased durability^{††}
- Improved ride and increased bead strength^{††}
- Choice of distinctive raised white letters on one sidewall and black outline serrated branding on the other





Tire Size	Service Desc.	Sidewall	MSPN	Stock #	Rim Width Range (inches)	Section Width on Measuring Rim Width ¹	Overall Dia.	Tread Depth (in/32nds)	Revs/Mile at 45 mph	Max Load (lbs@psi)	OE Fitment	Available
27x8.50R14/C	95Q	RWL	90127	439-838	6.0 - 7.5	8.5 on 7.0	26.6	16.0	782	1515@50		
LT215/75R15/C	100Q	RWL	71736	439-120	5.5 - 7.0	8.4 on 6.0	27.8	16.0	748	1765@50		
LT235/75R15/C	104Q	RWL	73110	439-127	6.0 - 7.0	9.1 on 6.5	29.0	16.0	717	1985@50		
30x9.50R15/C	104Q	RWL	50534	439-890	6.5 - 8.5	9.4 on 7.5	29.5	16.0	705	1990@50		
31x10.50R15/C	109Q	RWL	60316	439-895	7.0 - 9.0	10.5 on 8.5	30.7	16.5	677	2250@50	F	
LT325/60R15/C	106Q	RWL	41347**	439-360**	9.0 - 11.0	12.9 on 9.5	30.5	16.0	682	2095@35		
32x11.50R15/C	113Q	RWL	87811	439-924	8.0 - 10.0	11.4 on 9.0	31.7	17.0	656	2530@50		
33x10.50R15/C	114Q	RWL	75595	439-905	7.0 - 9.0	10.6 on 8.5	32.7	16.0	636	2620@50		
33x12.50R15/C	108Q	RWL	75406	439-943	8.5 - 11.0	12.4 on 10.0	32.7	17.0	636	2225@35		
33x9.50R15/C	113Q	RWL	95155	439-938	6.5 - 8.5	9.5 on 7.5	32.7	16.0	636	2510@50		
35x12.50R15/C	113Q	RWL	95210	439-972	8.5 - 11.0	12.7 on 10.0	34.7	17.0	599	2555@35		
LT215/70R16/C	100R	RWL	40954	439-427	5.5 - 7.0	8.7 on 6.5	28.0	16.0	743	1765@50		
LT225/70R16/C	102R	RWL	70688	439-631	6.0 - 7.0	8.9 on 6.5	28.5	16.0	730	1875@50		
LT225/75R16/D	110Q	RWL	45961	439-122	6.0 - 7.0	8.8 on 6.0	29.4	16.0	707	2335@65		
LT225/75R16/D	110S	RWL	64655	412-121	6.0 - 7.0	8.9 on 6.0	29.3	16.0	710	2335@65		
LT235/70R16/C	104Q	RWL	92965	439-138	6.0 - 7.5	9.5 on 7.0	29.1	16.0	715	1985@50		
LT235/85R16/E	120Q	RWL	41577	439-166	6.0 - 7.0	9.3 on 6.5	31.8	16.0	654	3042@80		
LT235/85R16/E	120S	RWL	61582	475-166	6.0 - 7.0	9.4 on 6.5	31.7	16.0	656	3042@80		
LT245/70R16/D	113Q	RWL	56856	439-444	6.5 - 7.5	9.7 on 7.0	29.6	16.0	703	2535@65		
LT245/70R16/D	113S	RWL	90649	412-444	6.5 - 7.5	9.8 on 7.0	29.5	16.0	705	2535@65		
LT245/75R16/E	120Q	RWL	84488	439-139	6.5 - 7.5	9.7 on 7.0	30.6	16.0	680	3042@80		
LT245/75R16/E	120S	RWL	10243	475-139	6.5 - 7.5	9.8 on 7.0	30.5	16.0	682	3042@80		
LT255/70R16/D	115Q	RWL	53876	439-265	6.5 - 8.0	10.2 on 7.5	30.2	16.0	689	2680@65		
LT265/70R16/D	117Q	RWL	41561	439-546	7.0 - 8.5	10.7 on 8.0	30.7	16.0	678	2835@65	T	
LT265/75R16/D	120S	RWL	61724	412-167	7.0 - 8.0	10.6 on 7.5	31.7	16.0	656	3042@65		
LT265/75R16/E	123Q	BSW	71887*	650-169*	7.0 - 8.0	10.5 on 7.5	31.8	15.0	654	3415@80		3Q
LT275/70R16/D	119Q	RWL	56638	439-545	7.0 - 8.5	11.0 on 8.0	31.3	16.0	665	3000@65		
LT275/70R16/D	119S	RWL	58521	479-545	7.0 - 8.5	11.1 on 8.0	31.2	16.0	667	3000@65		
LT285/75R16/D	122R	RWL	58739	475-185	7.5 - 9.0	11.4 on 8.0	32.8	17.0	634	3305@65		
LT285/75R16/E	126Q	BSW	87606*	650-668*	7.5 - 9.0	11.3 on 8.0	33.0	15.0	630	3750@80		3Q
LT295/75R16/D	123R	RWL	53444	475-454	7.5 - 9.5	11.5 on 8.0	33.2	17.0	626	3415@65		
LT305/70R16/D	118Q	RWL	90735	439-692	8.0 - 9.5	12.2 on 9.0	33.0	17.0	630	2910@50		
LT315/75R16/D	121Q	RWL	03643	412-322	8.0 - 10.0	12.2 on 8.5	34.6	17.0	601	3195@50		
31x10.50R16.5/D	116Q	RWL	77809	439-898	8.25 - 10.0	10.5 on 8.25	30.7	16.5	678	2745@65		
33x12.50R16.5/D	118Q	RWL	54758	439-947	8.25 - 10.5	12.3 on 9.75	32.7	17.0	634	2930@50		
33x12.50R16.5/D	118R	RWL	30537	412-947	8.25 - 10.5	12.4 on 9.75	32.6	17.0	638	2930@50		
35x12.50R16.5/D	123Q	RWL	55633	439-974	8.25 - 10.5	12.5 on 9.75	34.7	17.0	600	3415@50		
35x12.50R16.5/D	123R	RWL	98796	475-974	8.25 - 10.5	12.6 on 9.75	34.6	17.0	601	3415@50		
LT265/70R17/C	112Q	RWL	46621	439-446	7.0 - 8.5	10.7 on 8.0	31.8	16.0	654	2470@50		
LT285/70R17/D	121Q	BSW	58064*	534-604*	7.5 - 9.0	11.0 on 8.0	32.8	16.0	632	3195@65	DC	
LT285/70R17/D	121Q	RWL	57974	439-604	7.5 - 9.0	11.5 on 8.5	32.8	16.0	634	3195@65		
LT315/70R17/D	121R	BSW	54142*	400-984*	8.5 - 10.0	12.0 on 8.5	34.5	17.0	601	3195@50	GM	
37x12.50R17/D	124Q	RWL	99249	439-481	8.5 - 11.0	12.8 on 10.0	36.3	17.0	574	3525@50		
LT285/65R18/D	121Q	RWL	95290	439-907	8.0 - 10.0	11.5 on 8.5	32.8	16.0	634	3195@65		
LT285/55R20/D	117S	RWL	82915	475-292	8.0 - 10.0	11.7 on 9.0	32.5	15.0	640	2835@65		
LT325/60R20/D	121S	RWL	41857	475-295	9.0 - 12.0	13.0 on 9.5	35.5	15.0	586	3195@50		
37x12.50R20/D	120S	RWL	74497	475-271	8.5 - 11.0	12.5 on 10.0	36.6	15.0	568	3085@50		

Original Equipment Key: F = Ford, GM = General Motors, T = Toyota, DC = Daimler-Chrysler

††Compared to Radial All-Terrain T/A*

*Size does not meet the RMA requirements for severe snow conditions.

Government UTQG Ratings do not apply to light truck sized tires.

1. The dimensions shown are average values for tires measured on specified measuring rim width. Individual tires may vary from data shown.

2. Section width varies approximately 0.2" (5mm) for every 0.5" change in rim width.

WARNING: Serious or fatal injury may result from tire failure due to underinflation or overloading. To assure correct air pressure and vehicle load, refer to vehicle owner's manual or tire information placard on the vehicle. Serious injury or death may result from explosion of tire/rim assembly due to improper mounting. Only tire professionals should mount tires and they should never inflate beyond 40 psi to seat beads. Before mixing types of tires in any configuration on any vehicle, be sure to check the vehicle owner's manual for its recommendations.

DANGER: Never mount a 16" diameter tire on a 16.5" rim.

DANGER: Never mount a 17" diameter tire on a 17.5" rim.

Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a customer requests a replacement tire with a lower speed rating than the original equipment tire, you must clearly communicate to him or her that the handling of the vehicle may be different, and that its maximum speed capability is limited to that of the lowest speed rated tire on the vehicle. Exceeding the lawful speed limit is neither recommended nor endorsed.

